



From the Makers of Paint.

PROMASTER® Flat Interior Wall and Trim Paint 1271-XXXXV

DESCRIPTION

A professional quality flat latex wall and ceiling paint formulated to meet the requirements of painters, building managers, building contractors, interior decorators and architects. Formulated as a high-hiding product with good touch-up when applied by brush, roller or spray. Ideal for use on interior walls and ceiling surfaces in residential and commercial buildings, offices, schools and hospitals.

CERTIFICATIONS

AS OF 7/1/2009, COMPLIES WITH	
MPI#	N/A
LEED	Yes
CHPS	No
GREENGUARD	No
AIM	Yes
OTC/LADCO	Yes
CARB	Yes
SCAQMD	Yes

PERFORMANCE DATA

CHARACTERISTIC:	RESULTS:
Airless Spray Touch-Up*	★★★★★★★★☆☆
Dry Hide*	★★★★★★★★☆☆
Shim Scrub Resistance*	★★★☆☆☆☆☆☆
Washability*	★★★★★★☆☆☆☆
Sag Resistance	12-16 mils wet
Air and Substrate Application Temperature	50° F (10° C) - 90° F (32° C)
Service Temperature Limits	200° F (93° C)
Storage Temperature	40° (4° C) F - 95° F (35° C)

*Performance ratings are based on product comparisons to other products in that sheen range, performed at 77° F (25° C) 50% RH. Rating scale is from 1-10, 10 being the highest rating.

COMPOSITION

- Vinyl Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION DATA

Color:
White, ready mix & custom colors

Finish:
Flat, 1.8 units maximum @ 85°

Clean-up Solvent:
Soap & water

Density:
12.15 lbs/gal (1.46 kg/L)

VOC:
50 g/L (0.42 lbs/gal) maximum

Solids:
Volume - 32% ± 1%
Weight - 54% ± 1%

Theoretical Coverage @ 1 mil dry:
513 sq ft/gal (13 m²/L)

Practical Coverage:
Apply at 300-400 sq ft/gal (7-10 m²/L).
Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:
4.0 - 5.3 mils wet
1.3 - 1.7 mils dry

Flame Spread Rating:
Class A (0-25) over non-combustible surfaces

Flash Point:
None

Dry Time 77° F (25° C) & 50% RH:
To touch - 1 hour
To recoat - 2 hours

Shelf Life:
1 year minimum - unopened

ProMaster

9 FINISHES
PAINTING (09900)

Read Label and Material Safety Data Sheet Prior to Use. See other cautions on last page. DSF1-0690

SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, rust, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

NEW SURFACES: Drywall - Joint compound must dry for two days before priming. Prime with 1030 PVA Wall Primer Sealer. Product may be used self-priming on drywall, used as a primer under itself. Wood - Set nails, fill with latex spackle. Sand smooth. Dust clean. Prime with 3210 GRIPPER® Interior Exterior Primer Sealer or 1110 STAIN JAMMER® Alkyd Primer. Concrete, Plaster and Masonry - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Must be internally dry. Remove loose aggregate. Prime with 3030 Concrete Coatings Bond-Prep Pigmented Bonding Primer. Product may be used self-priming on concrete, used as a primer under itself. Fill concrete block with 3010 Concrete Coatings Block Filler. Prime plaster with 3210 GRIPPER Interior Exterior Primer Sealer. Steel - Performance over hand or power tool cleaned surfaces is dependent on the degree of cleaning. Prime with Devflex 4020PF Direct-to-Metal Primer, DEVGUARD® 4360 Low VOC Universal Primer or DEVGUARD 4160 Multi-Purpose Tank & Structural Primer.

Galvanized Metal and Aluminum - Clean off oils and other contaminants. Prime with 3210 GRIPPER Interior Exterior Primer Sealer, Devflex 4020PF Direct-to-Metal Primer, DEVGUARD 4360 Low VOC Universal Primer or DEVGUARD 4160 Multi-Purpose Tank & Structural Primer.

PREVIOUSLY PAINTED SURFACES: Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare areas with primer specified under NEW SURFACES.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

TINTING: Tint the appropriate base with DRAMATONE™ colorants.

SPREADING RATE: Apply at 300-400 sq ft/gal (7-10 m²/L) depending on surface texture and porosity. For best hiding, tint primers toward finish coat color. Certain shades of yellow, orange, pink and red may require multiple coats.

APPLICATION: Mix thoroughly before use. May be applied by brush, roller or spray. No thinning required. For airless spray, use a .015"-.017" tip. Adjust pressure as needed. Do not apply when

the surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying.

DRYING TIME: At 77°F (25°C) and 50% R.H., dries to touch in one-half hour and to recoat in two hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

CLEAN-UP: Clean immediately with warm, soapy water.

WASHING INSTRUCTIONS: Allow at least seven days after application before washing. Use non-abrasive, mild detergent and cellulose sponge.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS4-1105

SHIPPING

FREIGHT CLASSIFICATION:
Paint, Freezable

PACKAGING:
5 gallons (18.925 L)

FLASH POINT:
None

ProMaster



Akzo Nobel Paints LLC, Strongsville, Ohio 44136

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.