



# Roof Coating 100% Acrylic Elastomeric Exterior Flat Paint 2070-XXXX

Previously ICI Paints Roof Coating 100% Acrylic  
Elastomeric Exterior Flat

## DESCRIPTION

A premium quality 100% acrylic elastomeric coating specifically formulated to form a seamless membrane, which is resistant to sunlight, heat, ponded water and most chemicals. Typically used as a topcoat for roof coating systems or may be used as a stand alone product. While not intended as a roof replacement, it provides superior protection to built-up and gravel roof systems. May also be used on galvanized steel, concrete and urethane foam roofing, wood and composition shingles. Provides outstanding durability when used over urethane foam because of its ultraviolet protection and hailstone resistance.

## CERTIFICATIONS

AS OF 7/1/2009, COMPLIES WITH	
MPI#	N/A
LEED	N/A
CHPS	No
GREENGUARD	No
AIM	Yes
OTC/LADCO	Yes
CARB	Yes
SCAQMD	Yes



2070-XXXX ROOF COATING  
R1616 2 CEMENTS AND COATINGS FOR ROOFING  
SYSTEMS AS TO EXTERNAL FIRE EXPOSURE 57TK

## COMPOSITION

- 100% Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

## PERFORMANCE DATA

Property	Test Method	Results
Elongation	ASTM D 562	279%
Tensile Strength	ASTM D 2370	205 psi
Permeability	ASTM D 1653	9.26 perms
Adhesion to Polyurethane Foam	ASTM D 903	4.319 pli

## SPECIFICATION

Color:  
White (tintable, limit 1 oz/gal)

Clean-up Solvent:  
Soap and water

Finish: **Flat**  
Slight angular sheen

Density:  
12.15 lbs/gal (1.46 kg/L)

Solids:  
Volume - 52% +/- 1%  
Weight - 67% +/- 1%

VOC:  
50 g/L (0.42 lbs/gal) maximum  
Refer to MSDS for regulatory VOC content of complete product line

Theoretical Coverage @ 1 mil dry:  
836 sq ft/gal (20 m<sup>2</sup>/L)

Practical Coverage:  
Apply at 1-7/8 gallons per square or 54 sq ft/gal (1.3 m<sup>2</sup>/L).

Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:  
30 mils wet  
15 mils dry

Airless Spray Application:  
Pressure - Use a 30:1 pump and heavy duty gun  
Tip - .021" - .029" Reverse-a-Clean Tip

Dry Time 77°F (25°C) & 50% RH:  
To touch - 2 hours  
To recoat - 8 hours

Flame Spread Rating:  
Class A (0-25) on non-combustible surfaces

Flash Point:  
None

Shelf Life:  
1 year minimum - unopened



www.gliddenprofessional.com

9 FINISHES  
PAINTING (09900)



## SURFACE PREPARATION

### GENERAL SURFACE PREPARATION:

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint, rust scale and other foreign substances that may impair adhesion.

### NEW SURFACES:

#### Gravel Roofs:

- Must be sound and in good repair
- Slag or loose gravel should be removed

#### Metal Roofs:

- Prime with Devflex 4020PF Direct-to-Metal Primer

#### Foam Roofs:

- Must be smooth with no pinholes, ridges, edges or other substandard conditions

#### Concrete and Masonry:

- Prime with 3030 Concrete Coatings Bond-Prep Pigmented Bonding Primer
- Product may be used self-priming on concrete, used as a primer under itself

#### Wood and Composition Shingles:

- Prime with 6001 Hydrosealer Exterior Primer

### PREVIOUSLY PAINTED SURFACES:

- Wash to remove contaminants
- Rinse thoroughly with water and allow to dry
- Dull glossy areas by light sanding
- Remove sanding dust
- Remove loose paint
- Scrub heavy chalk areas with soap and water
- Remove all mildew by washing with a solution of 16 oz (473 mL) liquid household bleach and two oz (59 mL) non-ammoniated liquid detergent per gallon (3.785 L) of water
- Rinse surfaces clean with water and allow to dry for 24 hours
- Prime bare areas with primer specified under **NEW SURFACES**

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

## SHIPPING

### FREIGHT CLASSIFICATION:

Paint, Freezable

### PACKAGING:

5 gallons (18.925 L)

### FLASH POINT:

None

## DIRECTIONS FOR USE

### TINTING:

White may be tinted with up to one oz/gal of DRAMATONE™ colorants.

### SPREADING RATE:

Apply at 1-7/8 gallons per square or 54 sq ft/gal (1.3 m<sup>2</sup>/L), resulting in 15 mils dry (30 mils wet) per coat. Actual coverage may vary depending on substrate and application method.

### APPLICATION:

Mix thoroughly before use. No thinning required. Preferred method of application is by airless spray. Use a 30:1 pump and heavy duty gun with a .021-.029" reverse-a-clean tip. Adjust pressure as needed. When used as a roof system apply two coats in a cross hatch pattern, resulting in a total dry film thickness of 30 mils. May also be applied by brush or roller. Do not apply when the surface or air temperature is below 50°F (10°C) or if rain, snow or heavy dew is expected within 48 hours.

### DRYING TIME:

At 77°F (25°C) and 50% R.H., dries to touch in two hours and to recoat in eight hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

### CLEAN-UP:

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

## PRECAUTIONS

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.** DS4-1105



Akzo Nobel Paints LLC, Strongsville, Ohio 44136



www.gliddenprofessional.com

**LIMITATION OF LIABILITY** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. **WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE.** Liability, if any, is limited to replacement of the product or refund of the purchase price. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**